Name:	

Delaware Department of Agriculture Weights and Measures

Examination for Registered Fuel Dispenser Technicians

1.	The Delaware Weights and Measures Act is Title 6 Chapter	
2.	The Act gives weights and measures officials authority over the following equipment:	
	1. Devices used solely by a manufacturer for its own purposes	
	2. Devices used in the buying and/or selling of a product	
	3. Devices used only in fueling a fleet of company trucks and cars.	
3.	The test measures used by technicians are required to be certified by a certified NIST	
	laboratory:	
	1. As often as determined by the Department of Agriculture	
	2. Every two years	
	3. Every year	
	4. Every three years	
4.	Following an inspection and test, the weights and measures inspector has the authority to take the following official action:	
	1. Approve	
	2. Reject	
	3. Condemn and seize for evidence	
	4. All of the above	
5.	A registered service technician has the authority to:	
	1. Remove from a device an official weights and measures seal or tag	
	2. Take a device out of service when it is found to be out of tolerance	
	3. Place a device into commercial service following corrective service	
	4. All of the above	
6.	A registered service technician is required to notify weights and measures (send in a	
	Placed in Service Report) withinday (s) after placing a device into service	
7.	A registered service technician should have a current year Handbook	
8.	The General Code of Handbook 44 applies to all commercial devices. Paragraphs in Th General Code begin with the letter Paragraphs in the code for gas pumps begin with	

9.	Handbook 44 paragraphs are "retroactive" or "non-retroactive." In G-S.1., subparagraphs (a) and (b) are Subparagraphs (c), (d), (e), and (f) are
10.	All commercial devices must be marked with the name, initials or trademark of the (a) manufacturer and (b) the model designation. 1. True 2. False
11.	Dispensers at a service station are in error favorable to the owner/operator (test measure readings are minus). They are considered to be improperly maintained according to Paragraph G-UR
12.	Paragraph G-UR states that, "Whenever equipment is adjusted, the adjustments shall bring performance errors as close as practicable to ::
13.	Tolerances applied to devices being placed into service for the first time, being officially tested for the first time, after calibration, and following major service or overhaul is tolerance.
14.	Tolerances applied to devices in service that are being routinely tested istolerance.
15.	The requirement for the repeatability tolerance is
16.	The acceptance tolerance for a 5-gallon normal test or special test is±cu. in.
17.	The maintenance tolerance for a 10-gallon test is cu. in.
18.	 A reinforced discharge hose is required for retail fuel dispensers. 1. True 2. False
19.	In the event of a power loss, the information (dollars, gallons) indicated shall be retained at the dispenser or console for: 1. 15 minutes 2. 5 minutes 3. Not required to be retained
20.	An effective, shall be provided to prevent the draining

21.	For an accurate reading, the test measure must be level. A technician reads the bottom surface of the
22.	Retail dispensers and all attachment s (e.g. hoses, hose retractors, nozzles, displays, couplings, impact/fire valves, wiring, etc.) shall be maintained in proper operating condition throughout the term of service.
	(Paragraph G-UR)
23.	If provisions have been made for sealing (a physical seal), the device shall be sealed.
	(Paragraph <u>G-UR</u>)
24.	Indicator shall be of such character that they will not bend or become illegible.
	(Paragraph <u>G</u>)
25.	All Weights & Measures elements shall be so constructed, assembled, and installed so as not to facilitate fraud.
	(Paragraph <u>G</u> -

of the discharge hose between deliveries by the dispenser.